

This Safety Data Sheet cancels and replaces all preceding SDS for this product.

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

050001 106478

NATURAL & ARTIFICIAL FLAVOR (COGNAC TYPE)

© Firmenich product

1.2 Relevant identified uses of the substance or mixture and uses advised against

Concentrated aromatic raw material.

Not for personal use in this form or concentration.

For manufacturing use only.

1.3 Details of the supplier of the safety data sheet

Colin McIntosh, PhD; Chemist

Firmenich Inc.

P.O. Box 5880

Princeton - New Jersey 08543 - USA

colin.mcintosh@firmenich.com

Tel.:+1.609.452.10.00 - Fax.:+1.609.275.72.38

1.4 Emergency telephone number

FOR INFORMATION OR IN AN EMERGENCY CALL CHEMTREC @ 1-800-424-9300 or 1-703-527-3887.

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) N° 1272/2008 [CLP/GHS]

Flammable Liquid - Cat. 1 H224 Eye Irritation - Cat.2 H319 WARNING: CONTAINS VOLATILE FLAVORING CHEMICALS; BREATHING THESE CHEMICALS USH99 IN THE WORKPLACE MAY LEAD TO SEVERE LUNG DAMAGE.

2.1.2 Classification according to 67/548/EEC or 1999/45/EC

Symbols:

Highly flammable

Risks Phrases:

R11 Highly flammable.

2.1.3 Additional information

Full text of R- and S-phrases: see section 16

6181647

2.2 Label elements

US

Reference:

Date of printing: 28-MAR-2011

Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

Revised on: 01-Dec-2010 / v 6.1

1 / 12 Page



This Safety Data Sheet cancels and replaces all preceding SDS for this product.

Hazard pictograms:





Signal Word:

Danger

Hazard Statements:

H224 Extremely flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary Statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P235 Keep cool.

P240 Ground/bond container and receiving equipment.
P241 Use rated explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

Hazard Inducers:

Ethyl Acetate Ethyl Formate Iso-Butanol Propanal

2.3 Other hazards

WARNING: CONTAINS VOLATILE FLAVORING CHEMICALS; BREATHING THESE CHEMICALS IN THE WORKPLACE MAY LEAD TO SEVERE LUNG DAMAGE.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Mixture of aromatic substances.

6181647

Contains:

Reference:

US

Revised on: 01-Dec-2010 / v 6.1
Date of printing: 28-MAR-2011

Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

Page 2 / 12



This Safety Data Sheet cancels and replaces all preceding SDS for this product.

2.5 - 5.0% ethyl acetate

N° CAS: 0000141-78-6 / N° EINECS: 205-500-4

Classification: F Xi - R36,R67,R66,R11

GHS Classification: Eye Irritation - Cat.2

Specific Target Organ Toxicity - Single Exposure - Cat. 3 Narcotic Effects

2.5 - 5.0% ethyl formate

N° CAS: 0000109-94-4 / N° EINECS: 203-721-0

Classification: F Xn - R20/22,R36/37,R11

GHS Classification:

Acute Toxicity (inhalation) - Cat. 4 Acute Toxicity (oral) - Cat. 4

Eye Irritation - Cat.2

Specific Target Organ Toxicity - Single Exposure - Cat. 3 Respiratory Irritation

1.0 - 2.5% iso-butanol

N° CAS: 0000078-83-1 / N° EINECS: 201-148-0

Classification: Xi - R37/38,R41,R67,R10

GHS Classification: Eye Damage - Cat.1

Skin Irritation - Cat. 2

Specific Target Organ Toxicity - Single Exposure - Cat. 3 Narcotic Effects Specific Target Organ Toxicity - Single Exposure - Cat. 3 Respiratory Irritation

1.0 - 2.5% 1-Butanol, 3-methyl-

N° CAS: 0000123-51-3 / N° EINECS: 204-633-5

Classification: Xn - R37,R20,R10

GHS Classification:

Acute Toxicity (inhalation) - Cat. 4

Specific Target Organ Toxicity - Single Exposure - Cat. 3 Respiratory Irritation

0.1 - 0.5% 2-furaldehyde

N° CAS: 0000098-01-1 / N° EINECS: 202-627-7 Classification: T - R21,R23/25,R40,R36/37/38

GHS Classification:

Acute Toxicity (inhalation) - Cat. 2 Acute Toxicity (oral) - Cat. 3 Acute Toxicity (dermal) - Cat. 4

Eye Irritation - Cat.2 Skin Irritation - Cat. 2

Specific Target Organ Toxicity - Single Exposure - Cat. 3 Respiratory Irritation

Carcinogenicity - Cat. 2

4 FIRST-AID MEASURES

US

Reference:

4.1 Description of first aid measures

6181647

General information:

As in all cases of potential poisoning, Obtain medical advice immediately.

Date of printing: 28-MAR-2011
Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

Page 3 / 12

Revised on : 01-Dec-2010 / v 6.1



This Safety Data Sheet cancels and replaces all preceding SDS for this product.

In case of eye contact:

In the event of contact with the eyes, irrigate with water for at least 15 minutes; obtain medical advice if irritation persists.

In case of inhalation:

In the event of exposure to vapors, immediately remove from the area to a fresh air environment. Individuals showing evidence of inhalation exposure should be taken to an uncontaminated area. Obtain medical advice immediately.

In case of skin contact:

Remove contaminated clothes. Wash skin with large volumes of water.

If irritation persists, or any sign of tissue damage is apparent, obtain medical advice immediately.

In case of ingestion:

In the event of accidental ingestion, rinse mouth with water. Give up to one tumbler (half pint) of milk or water.

Obtain medical advise immediately.

Do not induce vomiting, obtain medical advise immediately.

4.2 Most important symptoms and effects, both acute and delayed

No information available on the product itself.

4.3 Indication of immediate medical attention and special treatment needed

None known.

5 FIRE-FIGHTING MEASURES

5.1 Extinguishing media

In the event of fire, adequate extinguishers should be used. Avoid inhalation of smoke and fumes. In case of insufficient ventilation, wear suitable respiratory equipment.

Cool fire exposed containers with water spray.

Extinguishing media: Foam, carbon dioxide or dry chemical.

5.2 Special hazard arising from the substance or mixture

Closed containers may build up pressure if exposed to heat (fire). Vapors form explosive mixtures with air and may travel to a source of ignition and flash back.

5.3 Advice for fire-fighters

No specific advice.

6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:

Adequate protective gloves should be worn when handling spillages. No smoking. Avoid naked flames or other potential sources of ignition (eg. electrical equipment).

Avoid skin contamination and inhalation of vapour.

Individual washing routines should be followed after any potential contact.

Ensure adequate ventilation in working areas following accidental releases.

For emergency personnel:

6181647

Reference:

US

Apply the same recommendations as section 6.1

Date of printing: 28-MAR-2011

Revised on: 01-Dec-2010 / v 6.1

Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

4 / 12 Page



This Safety Data Sheet cancels and replaces all preceding SDS for this product.

6.2 Environmental precautions

Do not discharge directly into drains, air, into soil or into the aquatic environment.

6.3 Methods and material for containment and cleaning up

For containment:

Eliminate all sources of ignition. Leaking containers should be removed to a well ventilated area if possible to do safely. If not, dike around container to limit spread of spill, leak. If spill/leak is small, clean up with standard absorbents (sand, vermiculite, etc.). Wear rubber gloves. Avoid contact with skin. If skin contact occurs, wash liberally with soap and water. See Section VI above. If large leak/spill, call HAZMAT Team. Vapors may cause vomiting and nausea. Wear appropriate respiratory protection.

For cleaning-up:

Spillages should be disposed of in accordance with Governmental Regulations.

7 HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Wear adequate protective gloves protection and eye/face protection.

No smoking. Avoid any sources of ignition.

Avoid exposing to high temperature during processing.

Do not ingest or apply to the skin as such. Good personal washing routines should be followed.

Maintain adequate local and general ventilation where product is handled.

7.1.1 Protective measures

Keep strict control of dust accumulation to a minimum. Maintain adequate local and general ventilation where product is handled. Avoid any sources of ignition.

7.1.2 Advice on general occupational hygiene

Good personal washing routines should be followed.

7.2 Conditions for safe storage, including any incompatibilities

It is good general practice to store in closed, preferably full, containers away from heat sources, and protected from extremes of temperature. Do not re-use the empty container.

Respect generals rules for compatibility storage.

7.3 Specific end use(s)

Not available at this time.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Reference:

US

0000141-78-6: ETHYL ACETATE (All forms)

6181647

NIOSH Recommended Exposure Limits (1994-JUN) TWA (1994-JUN): 400 ppm, 10 hours (All forms) TWA (1994-JUN): 1400 mg/m3, 10 hours (All forms)

0000109-94-4: ETHYL FORMATE (All forms) NIOSH Recommended Exposure Limits (1994-JUN)

Date of printing: 28-MAR-2011

Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

Revised on: 01-Dec-2010 / v 6.1

5 / 12 Page



This Safety Data Sheet cancels and replaces all preceding SDS for this product.

TWA (1994-JUN): 100 ppm, 10 hours (All forms) TWA (1994-JUN): 300 mg/m3, 10 hours (All forms)

0000141-78-6: Ethyl acetate (All forms) ACGIH Threshold Limit Values (1996-MAY)

TWA (1996-MAY): 400 ppm, 8 hours (All forms) TWA (1996-MAY): 1440 mg/m3, 8 hours (All forms)

0000141-78-6 : Ethyl acetate (All forms)

OSHA Permissible Exposure Limits (1989-MAR) TWA (1989-MAR): 400 ppm, 8 hours (All forms) TWA (1989-MAR): 1400 mg/m3, 8 hours (All forms)

0000141-78-6 : Ethyl acetate (All forms)

OSHA Permissible Exposure Limits, Table Z-1 Limits for Air Contaminants (1993-JUN)

TWA (1993-JUN): 400 ppm, 8 hours (All forms) TWA (1993-JUN): 1400 mg/m3, 8 hours (All forms)

0000109-94-4 : Ethyl formate (All forms) ACGIH Threshold Limit Values (1994-SEP)

TWA (1994-SEP): 100 ppm, 8 hours (All forms) TWA (1994-SEP): 303 mg/m3, 8 hours (All forms)

0000109-94-4 : Ethyl formate (All forms)

OSHA Permissible Exposure Limits (1989-MAR) TWA (1989-MAR): 100 ppm, 8 hours (All forms) TWA (1989-MAR): 300 mg/m3, 8 hours (All forms)

0000109-94-4 : Ethyl formate (All forms)

OSHA Permissible Exposure Limits, Table Z-1 Limits for Air Contaminants (1993-JUN)

TWA (1993-JUN): 100 ppm, 8 hours (All forms) TWA (1993-JUN): 300 mg/m3, 8 hours (All forms)

0000098-01-1: Furfural (All forms)

ACGIH Threshold Limit Values (1996-MAY) TWA (1996-MAY): 2 ppm, 8 hours (All forms) TWA (1996-MAY): 7.9 mg/m3, 8 hours (All forms)

0000098-01-1 : Furfural (All forms)

OSHA Permissible Exposure Limits (1989-MAR) TWA (1989-MAR): 2 ppm, 8 hours (All forms) TWA (1989-MAR): 8 mg/m3, 8 hours (All forms)

0000098-01-1: Furfural (All forms)

OSHA Permissible Exposure Limits, Table Z-1 Limits for Air Contaminants (1993-JUN)

TWA (1993-JUN): 5 ppm, 8 hours (All forms) TWA (1993-JUN): 20 mg/m3, 8 hours (All forms)

0000123-51-3: ISOAMYL ALCOHOL (PRIMARY) (All forms)

NIOSH Recommended Exposure Limits (1994-JUN) STEL (1994-JUN): 125 ppm, 15 minutes (All forms)

Revised on: 01-Dec-2010 / v 6.1 Reference: US 6181647 Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

> 6 / 12 Page

Date of printing: 28-MAR-2011



This Safety Data Sheet cancels and replaces all preceding SDS for this product.

STEL (1994-JUN): 450 mg/m3, 15 minutes (All forms) TWA (1994-JUN): 100 ppm, 10 hours (All forms) TWA (1994-JUN): 360 mg/m3, 10 hours (All forms)

0000078-83-1 : ISOBUTYL ALCOHOL (All forms)
NIOSH Recommended Exposure Limits (1994-JUN)
TWA (1994-JUN) : 50 ppm , 10 hours (All forms)
TWA (1994-JUN) : 150 mg/m3 , 10 hours (All forms)

0000123-51-3: Isoamyl alcohol (All forms) ACGIH Threshold Limit Values (1994-SEP)

STEL (1994-SEP): 125 ppm , 15 minutes (All forms) STEL (1994-SEP): 452 mg/m3 , 15 minutes (All forms) TWA (1994-SEP): 100 ppm , 8 hours (All forms) TWA (1994-SEP): 361 mg/m3 , 8 hours (All forms)

0000123-51-3: Isoamyl alcohol (primary and secondary) (All forms)

OSHA Permissible Exposure Limits (1989-MAR)

STEL (1989-MAR): 125 ppm, 15 minutes (All forms) STEL (1989-MAR): 450 mg/m3, 15 minutes (All forms) TWA (1989-MAR): 100 ppm, 8 hours (All forms) TWA (1989-MAR): 360 mg/m3, 8 hours (All forms)

0000078-83-1 : Isobutyl alcohol (All forms)
ACGIH Threshold Limit Values (1994-SEP)
TWA (1994-SEP) : 50 ppm 8 hours (All forms)

TWA (1994-SEP) : 50 ppm , 8 hours (All forms) TWA (1994-SEP) : 152 mg/m3 , 8 hours (All forms)

0000078-83-1: Isobutyl alcohol (All forms)
OSHA Permissible Exposure Limits (1989-MAR)
TWA (1989-MAR): 50 ppm, 8 hours (All forms)
TWA (1989-MAR): 150 mg/m3, 8 hours (All forms)

0000078-83-1: Isobutyl alcohol (All forms)

OSHA Permissible Exposure Limits, Table Z-1 Limits for Air Contaminants (1993-JUN)

TWA (1993-JUN) : 100 ppm , 8 hours (All forms) TWA (1993-JUN) : 300 mg/m3 , 8 hours (All forms)

0000123-51-3: Isomyl alcohol (primary and secondary) (All forms)

OSHA Permissible Exposure Limits, Table Z-1 Limits for Air Contaminants (1993-JUN)

TWA (1993-JUN): 100 ppm, 8 hours (All forms) TWA (1993-JUN): 360 mg/m3, 8 hours (All forms)

8.2 Exposure controls

US

Reference:

Avoid exposing to high temperature during processing.

Maintain adequate local and general ventilation where product is handled.

8.2.1 Appropriate engineering controls

6181647

Maintain adequate local and general ventilation where product is handled and dispensed.

Date of printing: 28-MAR-2011
Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

Page 7 / 12

Revised on : 01-Dec-2010 / v 6.1



This Safety Data Sheet cancels and replaces all preceding SDS for this product.

8.2.2 Environmental exposure controls

Not available at this time. Minimize release to the environment.

8.3 Personal protection

Respiratory protection: Breathing of the vapors or dust particles may be hazardous. In the absence of appropriate engineering controls such as spot ventilation, ventilated enclosures, etc., workers should avail themselves of the appropriate NIOSH approved respiratory protection.

Hand protection: Adequate Protective Gloves should be worn.

Eye protection: Adequate safety glasses should be used.

Skin protection: Wear protective clothing, overall if necessary to limit the odour contamination of personal

clothing. Individual washing routines should be followed after any potential contact.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance: LIQUID Colour: **BROWN**

Odour: Characteristic strong odour

according to the commercial description of the substance.

pH: Not available Melting point/range (°C): Not available Initial boiling point/range (°C): Not available

Flash point (closed cup): = 61 Fahrenheit (= 16 Centigrade)

Evaporation rate: Not available Flammability (solid/gas): Not available Upper/lower flammability or explosive Not available

Vapor pressure (At 20°C in mm Hg)

Calculated vapor pressure (At 20°C 27.4

in mm Hg):

Vapour density: Not available Relative density (d 20/20): 0.962 - 1.01 Water solubility (20°C): Not applicable Partition coef. (n-octanol/water): Not applicable Auto-ignition temperature (°C): Not available Decomposition temperature: Not available Viscosity: Not available Not available Explosive properties: Oxidizing properties: Not available VOC Content less than: 27%

10 STABILITY AND REACTIVITY

10.1 Reactivity

Reference:

No reaction known with water.

10.2 Chemical stability

US

6181647 Date of printing: 28-MAR-2011 Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

> 8 / 12 Page

Revised on: 01-Dec-2010 / v 6.1



This Safety Data Sheet cancels and replaces all preceding SDS for this product.

Presents no significant reactivity hazard. Normally stable even at elevated temperatures and pressures. Avoid temperatures above or near to the flash point. Not pyrophoric nor reactive with water. Does not undergo explosive decomposition, is shock stable, and is not an oxygen donor. Does not form explosive mixtures with other organic materials. Will not undergo hazardous exothermic polymerization.

10.3 Possibility of hazardous reactions

Not known.

10.4 Conditions to avoid

Avoid temperatures above or at least 5 °C below flash point for any flammable liquids.

Do not heat closed containers.

Avoid contact with oxidizing agents.

10.5 Incompatible materials

Avoid strong oxidizing agents.

10.6 Hazardous decomposition products

Contact with water or storage under recommended conditions for one year should not produce dangerous decomposition products.

11 TOXICOLOGICAL INFORMATION

This preparation has not been subjected to toxicological testing as an entity but has been blended from materials with established toxicological bibliographies. In view of the difficulty of using current standard toxicological evaluation techniques to predict potential hazards to susceptible individuals or arising from unforeseeable potentiation, this preparation should be considered and handled as if it displayed health hazards and treated in consequence with all possible precaution.

12 ECOLOGICAL INFORMATION

This preparation has not been subjected to ecotoxicological testing as an entity. In view of the difficulty of using current standard ecotoxicological evaluation techniques to predict the impact of particular modes of release on vulnerable or localised parts of the ecosystem, this preparation should be considered and handled as if it displayed potential environmental hazards, and treated in consequence with all possible precaution.

13 DISPOSAL CONSIDERATIONS

Empty all containers using a two stage pumping system or draining until no free liquid remains Minimize release to the environment.

14 TRANSPORT INFORMATION

In case of accidental spillage or fire during transport, refer to instructions given under points 5, 6, 7 and 8 above.

14.1 UNO

Reference:

US

UN-No: 1197

6181647

Proper Shipping Name: EXTRACTS, FLAVOURING, LIQUID

Class: 3 Packing Group: II

Date of printing: 28-MAR-2011
Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

Page 9 / 12

Revised on : 01-Dec-2010 / v 6.1



This Safety Data Sheet cancels and replaces all preceding SDS for this product.

14.2 Land transport (ADR/RID)

UN-No: 1197

Proper Shipping Name: EXTRACTS, FLAVOURING, LIQUID (VAPOUR PRESSURE AT 50°C MORE

THAN 110 KPA)

Class: 3 Packing group: II

14.3 Sea transport (IMDG-Code)

UN-No: 1197

Proper Shipping Name: EXTRACTS, FLAVOURING, LIQUID

Class: 3 Packing group: II

14.4 Air transport (ICAO-IATA)

UN-No: 1197

Proper Shipping Name: EXTRACTS, FLAVOURING, LIQUID

Class: 3 Packing group: II

15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

NFPA Hazard Classification

Health: 2 Flammability: 3 Reactivity: 0

This mixture contains no toxic chemical or chemicals subject to reporting requirements of Section 313 of Title III of the Superfund Amendements and Reauthorization Act of 1986 and 29 CFR Part 1910.1200.

15.2 Chemical Safety Assessment

No data available at this time.

16 OTHER INFORMATION

16.1 Revisions

Reference:

01-Dec-2010: Version 1.0 - First version validated for publication

16.2 Key literature references

RIFM database OECD SIDS EU IUCLID

US

Supplier information

16.3 Risk & Safety Phrases used under section 2

6181647

Date of printing: 28-MAR-2011
Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

Revised on: 01-Dec-2010 / v 6.1

Product : 050001 106478 - NATURAL & ARTIFICIAL FL

Page 10 / 12



This Safety Data Sheet cancels and replaces all preceding SDS for this product.

R11 Highly flammable.

S16 Keep away from sources of ignition - No smoking.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P235 Keep cool.

P240 Ground/bond container and receiving equipment.
P241 Use rated explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use appropriate fire extinguishers for fire control. Store in a well-ventilated place. Keep container tightly closed.

16.4 Risk Phrases used under section 3

Reference:

US

6181647

R10 Flammable.
R11 Highly flammable.
R20 Harmful by inhalation.

R20/22 Harmful by inhalation and if swallowed.

R21 Harmful in contact with skin.

R23/25 Toxic by inhalation and if swallowed.

R36 Irritating to eyes.

R36/37 Irritating to eyes and respiratory system.
R36/37/38 Irritating to eyes, respiratory system and skin.

R37 Irritating to respiratory system.

R37/38 Irritating to respiratory system and skin.

R40 Limited evidence of a carcinogenic effect.

R41 Risk of serious damage to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Revised on : 01-Dec-2010 / v 6.1

Date of printing: 28-MAR-2011

Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

Page 11 / 12



This Safety Data Sheet cancels and replaces all preceding SDS for this product.

We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Firmenich, it is the user's obligation to determine conditions of safe use of the product.

Information contained in this document and related material is proprietary to Firmenich. Disclosure to third parties without the prior written consent of Firmenich except where required by applicable laws and regulations and/or reverse engineering are strictly prohibited.

Revised on: 01-Dec-2010 / v 6.1 Date of printing: 28-MAR-2011

Product: 050001 106478 - NATURAL & ARTIFICIAL FLA

Page 12 / 12

Reference :

US

6181647