

Product OPOPONAX RESIN ABS 50 PCT

Print Date

03/09/2011

Page 1 (8)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name Sales ID MSDS Number Product Use Description	:	OPOPONAX RESIN ABS 50 PCT 00156775 R00000003189 Fragrance Ingredient
Company	:	IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ
Telephone Telefax Emergency telephone	: : :	+34964470212 +34964473411 +34 964 470 212

### SECTION 2 HAZARDS IDENTIFICATION

OSHA Hazards

: Mild skin irritant Mild eye irritant

#### Carcinogenicity:

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Version	
Revision	Date

: 3 : 01/13/2010

IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ

Telephone: +34964470212



ProductOPOPONAX RESIN ABS 50 PCTPrint Date03/09/2011Page 2 (8)

## SECTION 4. FIRST AID MEASURES

First aid procedures		
Inhalation	:	Remove from exposure site to fresh air and keep at rest. Obtain medical advice.
Skin contact	:	Remove contaminated clothes. Wash thoroughly with water (and soap). Contact physician if symptoms persist.
Eye contact	:	Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.
Ingestion	:	Rinse mouth with water and obtain medical advice.

SECTION 5. FIRE-FIGHTING MEASURES			
Flammable properties			
Flash point	:	212.00 °F (100.00 °C)	
Fire fighting			
Suitable extinguishing media	:	Use water spray, dry chemical, carbon dioxide or appropriate foam.	
Protective equipment and precautions for firefighters			
Special protective equipment for fire-fighters	:	Wear NIOSH approved self-contained breathing apparatus and full protective clothing when fighting fires involving chemicals. Use water spray to cool containers exposed to fire.	

Version Revision Date : 3 : 01/13/2010

IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ

Telephone: +34964470212

IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ

Telefax: +34964473411



Product **OPOPONAX RESIN ABS 50 PCT** Print Date 03/09/2011

Page 3 (8)

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions	:	Avoid inhalation and contact with skin and eyes. A self- contained breathing apparatus is recommended in case of a major spill.
Environmental precautions	:	Keep away from drains, surface- and groundwater and soil.
Methods for containment / Methods for cleaning up	:	Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

## SECTION 7. HANDLING AND STORAGE

Handling	:	Avoid excessive inhalation of concentrated vapors. Follow good manufacturing practices for housekeeping and personal hygiene. Wash any exposed skin immediately after any chemical contact, before breaks and meals, and at the end of each work period. Contaminated clothing and shoes should be thoroughly cleaned before re-use.
		If appropriate, procedures used during the handling of this material should also be used when cleaning equipment or removing residual chemicals from tanks or other containers, especially when steam or hot water is used, as this may increase vapor concentrations in the workplace air. Where chemicals are openly handled, access should be restricted to properly trained employees. Keep all heated processes at the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.
Advice on protection against fire and explosion	:	Keep away from ignition sources and naked flame.
Requirements for storage areas and containers	:	Store in a cool, dry, ventilated area away from heat sources. Keep containers upright and tightly closed when not in use.
Version Revision Date		: 3 : 01/13/2010
IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ		IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ

Telephone: +34964470212



Product OPOPONAX RESIN ABS 50 PCT

Print Date

03/09/2011

Page 4 (8)

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	Listed by	Value type	Exposure limit(s)
1,2- Benzenedicarboxy lic acid, diethyl ester	US. American Conference of Governmental and Industrial Hygienists Threshold Limit Values for Chemical Substances in the Work Environment; Annual Reports for the Year 2004:Committees on Threshold Limit Values (TLVs ) and Biological Exposure Indices (BEIs)	TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level	5 mg/m3
1,2- Benzenedicarboxy lic acid, diethyl ester	US. Department of Labor - Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1000 Z-1-A	PEL: Permissible Exposure Level	5 mg/m3

#### **Engineering measures**

Engineering measures : Where feasible, isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under negative air pressure relative to the rest of the plant. Where feasible, use closed systems to transfer and process this material

#### Personal protective equipment

Eye protection	: Use tight-fitting goggles, face shield or safety glasses with side shields if eye contact might occur.
Hand protection	: Avoid skin contact. Use chemically resistant gloves.
Respiratory protection	: Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid

Version Revision Date : 3 : 01/13/2010

IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ

Telephone: +34964470212



Product	OPOPONAX RESIN ABS 50 PCT		
Print Date	03/09/2011	Page	5 (8)

	excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures. No respiratory protection is required during normal operations in a workplace where engineering controls such as adequate ventilation, etc. are sufficient.
	If engineering controls and safe work practices are not sufficient, an approved, properly fitted respirator with organic vapor cartridges or canisters and particulate filters should be used:
	<ul> <li>a)while engineering controls and appropriate safe work practices and/or procedures are being implemented; or b)during short term maintenance procedures when engineering controls are not in normal operation or are not sufficient; or</li> <li>c)if normal operational workplace vapor concentration in the air is increased due to heat ;</li> <li>d)during emergencies; or</li> <li>e)if engineering controls and operational practices are not sufficient to reduce airborne concentrations below an established occupational exposure limit.</li> </ul>
Hygiene measures :	To the extent deemed appropriate, implement pre-placement and regularly scheduled ascertainment of symptoms and spirometry testing of lung function for workers who are regularly exposed to this material. To the extent deemed appropriate, use an experienced air sampling expert to identify and measure volatile chemicals that could be present in the workplace air to determine potential exposures and to ensure the continuing effectiveness of engineering controls and operational practices to minimize exposure.
Protective measures :	In December 2003, the National Institute for Occupational Safety and Health ("NIOSH") published an Alert on preventing lung disease in workers who use or make flavorings [NIOSH Publication Number 2004-110].

Version Revision Date : 3 : 01/13/2010

IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ

Telephone: +34964470212



Product	OPOPONAX RESIN ABS 50 PCT		
Print Date	03/09/2011	Page	6 (8)

In August 2004, the United States Flavor and Extract Manufacturers Association (FEMA) issued a report entitled "Respiratory Safety in the Flavor Manufacturing Workplace". Both of these reports provide recommendations for reducing employee exposure and for medical surveillance in the workplace. The recommendations in these reports are generally applicable to the use of any chemical in the workplace and you are strongly urged to review both of these reports. The report published by FEMA also contains a list of "high priority" chemicals. If any of these chemicals are present in

priority" chemicals. If any of these chemicals are present in this product at a concentration >= 1.0% due to an intentional addition by IFF, the chemical(s) will be identified in this safety data sheet.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical state Colour	: liquid : reddish tan
Odour	: Conforms to Standard
Safety data	
Flash point	: 212.00 °F (100.00 °C)
Vapour pressure	: .02 hPa (0.02 mmHg) Note: Calculated
Relative density (20 °C)	: 1.0330 - 1.1160

## SECTION 10. STABILITY AND REACTIVITY

Chemical stability

: Remarks: Presents no significant reactivity hazard, by itself or

Version Revision Date : 3 : 01/13/2010

IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ

Telephone: +34964470212



Product	OPOPONAX RESIN ABS 50 PCT	
Print Date	03/09/2011	Page 7 (8)
	in contact with water. Avoid contact with strong oxidizing agents.	acids, alkali or
Hazardous decomposition products	: Note: Carbon monoxide and unidentified organi- may be formed during combustion.	c compounds

### SECTION 11. TOXICOLOGICAL INFORMATION

#### **Toxicological information**

Further information	:	There is no data available for this product. The health hazards
		are assessed based on the ingredients in this preparation and
		their concentrations.

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecological information

Additional ecological : Avoid contamination of soil, ground and surface water. information

## SECTION 13. DISPOSAL CONSIDERATIONS

Contaminated packaging : Place material into sealed containers and dispose of in accordance with local, state and federal regulations.

#### SECTION 14. TRANSPORT INFORMATION

- DOT Not dangerous goods
- IATA Not dangerous goods
- IMDG Not dangerous goods

Version Revision Date : 3 : 01/13/2010

IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ

Telephone: +34964470212



ProductOPOPONAX RESIN ABS 50 PCTPrint Date03/09/2011Page 8 (8)

### SECTION 15. REGULATORY INFORMATION

OSHA Hazards SARA 311/312 Hazards		Mild skin irritant, Mild eye irritant Acute Health Hazard
Reportable Quantity HMIS Classification	:	Health Hazard: 1 Flammability: 1 Physical and chemical hazards: 0

## SECTION 16. OTHER INFORMATION

#### **Further information**

The information in this MSDS was obtained from current and reliable sources. However the data is provided without any warrant, expressed or implied, regarding its correctness or accuracy. Since the use, handling, storage and disposal of this product are beyond IFF control, it is the responsibility of the user both to determine safe conditions for the use of this product and to assume liability of loss, damage, or expense arising out of the product's improper use. No warranty expressed or implied regarding the product described herein shall be created by or inferred from any statement or omission in this MSDS. Various Federal, State or Provincial agencies may have specific regulations concerning the transportation, handling, storage, use, or disposal of this product which may not be reflected in this MSDS. The user should review these regulations to ensure full compliance.

Version Revision Date : 3 : 01/13/2010

IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ

Telephone: +34964470212

IFF Benicarló, S.A. Avda. Felipe Klein 2 12580 BENICARLÓ

Telefax: +34964473411