According to Regulation HCS 2012

This Safety Data Sheet cancels and replaces all preceding SDS for this product.

## **1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

1.1 Product identifier

**597937 A** ARTIFICIAL GRAPE FLAVOR © Firmenich product

1.2 Relevant identified uses of the substance or mixture and uses advised against

Ingredient for use in products that may be ingested. Not for personal use in this form or concentration. Intended to be used in the manufacture of products for consumers.

#### 1.3 Details of the supplier of the safety data sheet

Mr. Thomas Sulich Firmenich Inc. P.O. Box 5880 Princeton - New Jersey 08543 - USA thomas.sulich@firmenich.com Tel.:+1.609.452.10.00 - Fax.:+1.609.275.72.38

1.4 Emergency telephone number

FOR INFORMATION OR IN AN EMERGENCY CALL CHEMTREC @ 1-800-424-9300 or 1-703-527-3887.

## **2 HAZARDS IDENTIFICATION**

2.1 Classification of the substance or mixture

According to Regulation HCS 2012

Flammable Liquid - Cat. 2	H225
Skin Irritation - Cat. 2	H315
Eye Irritation - Cat.2A	H319

#### Additional information

Full text of listed statements : See section 16

## 2.2 Label elements

Hazard pictograms:

According to Regulation HCS 2012

This Safety Data Sheet cancels and replaces all preceding SDS for this product.



Signal Word: Danger

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

## **Precautionary Statements:**

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P264	Wash thoroughly after handling.
P240	Ground/bond container and receiving equipment.
P241	Use rated explosion-proof electrical equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

## 2.3 Other hazards

CAUTION: THIS MATERIAL CONTAINS VOLATILE FLAVORING CHEMICALS IDENTIFIED IN THE FEMA "RESPIRATORY HEALTH AND SAFETY MANUFACTURING WORKPLACE" DOCUMENT. No data available at this time.

## **<u>3 COMPOSITION/INFORMATION ON INGREDIENTS</u>**

The exact percentage (concentration) of composition has been withheld as a trade secret.

## 3.2 Mixture

Mixture of aromatic substances.

Contains :

## According to Regulation HCS 2012

This Safety Data Sheet cancels and replaces all preceding SDS for this product.

>= 10.0 < 15.0% Ethyl Acetate N° CAS : 0000141-78-6 N° EINECS: 205-500-4	Classification: F Xi - R36,R67,R11 GHS Classification: Specific Target Organ Toxicity - Single Exposure - Cat. 3 Narcotic Effects [H336] Eye Irritation - Cat.2A [H319] Flammable Liquid - Cat. 2 [H225]
>= 10.0 < 15.0% Benzoic Acid, 2-Amino-, Methyl Ester N° CAS : 0000134-20-3 N° EINECS: 205-132-4	Classification: Xi - R36 GHS Classification: Eye Irritation - Cat.2A [H319]
>= 7.5 < 10.0% 4h-Pyran-4-One, 2- Ethyl-3-Hydroxy- N° CAS : 0004940-11-8 N° EINECS: 225-582-5	Classification: Xn - R22 GHS Classification: Acute Toxicity (oral) - Cat. 4 [H302]
>= 5.0 < 7.5% Acetic Acid N° CAS : 0000064-19-7 N° EINECS: 200-580-7	Classification: C - R35,R10 GHS Classification: Skin Corrosion - Cat. 1A [H314] Eye Damage - Cat.1 [H318] Flammable Liquid - Cat. 3 [H226]
>= 5.0 < 7.5% Butanoic Acid, 3- Methylbutyl Ester N° CAS : 0000106-27-4 N° EINECS: 203-380-8	Classification: - R52/53,R10 GHS Classification: Environmental Hazard (chronic) - Cat. 3 [H412] Flammable Liquid - Cat. 3 [H226]
>=2.5 < 5.0% Isopentyl Acetate N° CAS : 0000123-92-2 N° EINECS: 204-662-3	Classification: - R10 GHS Classification: Flammable Liquid - Cat. 3 [H226]
>= 1.0 < 2.5% Butanoic Acid, 3-Methyl-, Ethyl Ester N° CAS : 0000108-64-5 N° EINECS: 203-602-3	Classification: Xi - R38,R10 GHS Classification: Skin Irritation - Cat. 2 [H315] Flammable Liquid - Cat. 3 [H226]

## According to Regulation HCS 2012

#### This Safety Data Sheet cancels and replaces all preceding SDS for this product.

>= 1.0 < 2.5%	Classification: C - R34
Hexanoic Acid	GHS Classification:
N° CAS : 0000142-62-1	Skin Corrosion - Cat. 1C [H314]
N° EINECS: 205-550-7	Eye Damage - Cat.1 [H318]
>= 0.1 < 0.5%	Classification: Xi - R43,R38,R41
2,6-Octadien-1-Ol, 3,7-	GHS Classification:
Dimethyl-, (E)-	Eye Damage - Cat.1 [H318]
N° CAS : 0000106-24-1	Skin Sensitization - Cat. 1B [H317]
N° EINECS: 203-377-1	Skin Irritation - Cat. 2 [H315]
0 < 0.1% 2-Buten-1-One, 1- (2,6,6-Trimethyl-1,3- Cyclohexadien-1-Yl)- N° CAS : 0023696-85-7	Classification: Xi N - R43,R51/53 GHS Classification: Skin Sensitization - Cat. 1A [H317] Environmental Hazard (chronic) - Cat. 2 [H411]

## 4 FIRST-AID MEASURES

N° EINECS: 245-844-2

4.1 Description of first aid measures

General information:

As in all cases of potential poisoning, Obtain medical advice immediately.

In case of eye contact:

In the event of contact with the eyes, irrigate with water for at least 15 minutes; obtain medical advice if irritation persists.

In case of inhalation:

In the event of exposure to vapors, immediately remove from the area to a fresh air environment. Individuals showing evidence of inhalation exposure should be taken to an uncontaminated area. Obtain medical advice immediately.

In case of skin contact:

Remove contaminated clothes. Wash skin with large volumes of water. If irritation persists, or any sign of tissue damage is apparent, obtain medical advice immediately.

In case of ingestion:

In the event of accidental ingestion, rinse mouth with water. Give up to one tumbler (half pint) of milk or water. Obtain medical advise immediately.

Do not induce vomiting, obtain medical advise immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No information available on the product itself.
- 4.3 Indication of immediate medical attention and special treatment needed None known.

## According to Regulation HCS 2012

This Safety Data Sheet cancels and replaces all preceding SDS for this product.

## **5 FIRE-FIGHTING MEASURES**

## 5.1 Extinguishing media

In the event of fire, adequate extinguishers should be used. Avoid inhalation of smoke and fumes. In case of insufficient ventilation, wear suitable respiratory equipment.

Cool fire exposed containers with water spray.

Extinguishing media: Foam, carbon dioxide or dry chemical.

5.2 Special hazard arising from the substance or mixture

Closed containers may build up pressure if exposed to heat (fire). Vapors form explosive mixtures with air and may travel to a source of ignition and flash back.

5.3 Advice for fire-fighters

No specific advice.

## **6 ACCIDENTAL RELEASE MEASURES**

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:

Adequate protective gloves should be worn when handling spillages. No smoking. Avoid naked flames or other potential sources of ignition (eg. electrical equipment).

Avoid skin contamination and inhalation of vapour.

Individual washing routines should be followed after any potential contact.

Ensure adequate ventilation in working areas following accidental releases.

For emergency personnel: Apply the same recommendations as section 6.1

6.2 Environmental precautions

Do not discharge directly into drains, air, into soil or into the aquatic environment.

## 6.3 Methods and material for containment and cleaning up

#### For containment:

Eliminate all sources of ignition. Leaking containers should be removed to a well ventilated area if possible to do safely. If not, dike around container to limit spread of spill, leak. If spill/leak is small, clean up with standard absorbents (sand, vermiculite, etc.). Wear rubber gloves. Avoid contact with skin. If skin contact occurs, wash liberally with soap and water. See Section VI above. If large leak/spill, call HAZMAT Team.

For cleaning-up:

Spillages should be disposed of in accordance with Governmental Regulations.

## 7 HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Wear adequate protective gloves protection and eye/face protection.

No smoking. Avoid any sources of ignition.

Avoid exposing to high temperature during processing.

Do not ingest or apply to the skin as such. Good personal washing routines should be followed.

Maintain adequate local and general ventilation where product is handled.

## According to Regulation HCS 2012

This Safety Data Sheet cancels and replaces all preceding SDS for this product.

Protective measures

Keep strict control of dust accumulation to a minimum.Maintain adequate local and general ventilation where product is handled.Avoid any sources of ignition.

### Advice on general occupational hygiene

Good personal washing routines should be followed.

## 7.2 Conditions for safe storage, including any incompatibilities

It is good general practice to store in closed, preferably full, containers away from heat sources, and protected from extremes of temperature. Do not re-use the empty container. Respect generals rules for compatibility storage.

7.3 Specific end use(s)

Not available at this time.

## **8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

## 8.1 Control parameters

0000064-19-7 : ACETIC ACID (All forms) National Institute for Occupational Safety and Health (NIOSH) Recommended Exposure Limits (REL) (2010-SEP) STEL (1994-JUN) : 15 ppm , 15 minutes (All forms) STEL (1994-JUN) : 37 mg/m3 , 15 minutes (All forms) TWA (1994-JUN) : 10 ppm , 10 hours (All forms) TWA (1994-JUN) : 25 mg/m3 , 10 hours (All forms) 0000064-19-7 : Acetic acid (All forms) American Conference of Governmental Industrial Hygienists (ACGIH) - Threshold Limit Values (TLV) (1994-SEP) STEL (1994-SEP) : 15 ppm , 15 minutes (All forms) STEL (1994-SEP) : 37 mg/m3 , 15 minutes (All forms) TWA (1994-SEP) : 10 ppm , 8 hours (All forms)

TWA (1994-SEP) : 25 mg/m3 , 8 hours (All forms)

0000064-19-7 : Acetic acid (All forms)

Occupational Safety and Health Administration (OSHA) (29 CFR 1910.1000 Z-1-A) - Permissible Exposure Limits - 1989 vacated values (1989-MAR)

TWA (1989-MAR) : 10 ppm , 8 hours (All forms) TWA (1989-MAR) : 25 mg/m3 , 8 hours (All forms)

0000064-19-7 : Acetic acid (All forms)

Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1001 to 1910.1048 - Substance-Specific Standards (1993-JUN)

TWA (1993-JUN) : 10 ppm, 8 hours (All forms)

TWA (1993-JUN) : 25 mg/m3 , 8 hours (All forms)

0000141-78-6 : ETHYL ACETATE (All forms)

National Institute for Occupational Safety and Health (NIOSH) Recommended Exposure Limits (REL) (2010-SEP)

TWA (1994-JUN) : 400 ppm , 10 hours (All forms)



## According to Regulation HCS 2012

This Safety Data Sheet cancels and replaces all preceding SDS for this product.

TWA (1994-JUN) : 1400 mg/m3 , 10 hours (All forms) 0000141-78-6 : Ethyl acetate (All forms) American Conference of Governmental Industrial Hygienists (ACGIH) - Threshold Limit Values (TLV) (2012-MAR) TWA (1996-MAY) : 400 ppm , 8 hours (All forms) TWA (1996-MAY) : 1440 mg/m3, 8 hours (All forms) 0000141-78-6 : Ethyl acetate (All forms) Occupational Safety and Health Administration (OSHA) (29 CFR 1910.1000 Z-1-A) - Permissible Exposure Limits - 1989 vacated values (1989-MAR) TWA (1989-MAR) : 400 ppm , 8 hours (All forms) TWA (1989-MAR) : 1400 mg/m3, 8 hours (All forms) 0000141-78-6 : Ethyl acetate (All forms) Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1001 to 1910.1048 - Substance-Specific Standards (1993-JUN) TWA (1993-JUN) : 400 ppm , 8 hours (All forms) TWA (1993-JUN) : 1400 mg/m3 , 8 hours (All forms) 0000123-92-2 : ISOAMYL ACETATE (All forms) National Institute for Occupational Safety and Health (NIOSH) Recommended Exposure Limits (REL) (2010-SEP) TWA (1994-JUN) : 100 ppm , 10 hours (All forms) TWA (1994-JUN) : 525 mg/m3 , 10 hours (All forms) 0000123-92-2 : Isoamyl acetate (All forms) American Conference of Governmental Industrial Hygienists (ACGIH) - Threshold Limit Values (TLV) (2000-MAR) STEL (2000-MAR) : 100 ppm , 15 minutes (All forms) TWA (2000-MAR) : 50 ppm , 8 hours (All forms) 0000123-92-2 : Isoamyl acetate (All forms) Occupational Safety and Health Administration (OSHA) (29 CFR 1910.1000 Z-1-A) - Permissible Exposure Limits - 1989 vacated values (1989-MAR) TWA (1989-MAR) : 100 ppm , 8 hours (All forms) TWA (1989-MAR) : 525 mg/m3, 8 hours (All forms) 0000123-92-2 : Isomyl acetate (All forms) Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1001 to 1910.1048 - Substance-Specific Standards (1993-JUN) TWA (1993-JUN) : 100 ppm , 8 hours (All forms) TWA (1993-JUN) : 525 mg/m3 , 8 hours (All forms) 8.2 Exposure controls Avoid exposing to high temperature during processing. Maintain adequate local and general ventilation where product is handled.

Appropriate engineering controls

Maintain adequate local and general ventilation where product is handled and dispensed.

## According to Regulation HCS 2012

This Safety Data Sheet cancels and replaces all preceding SDS for this product.

### Environmental exposure controls

Not available at this time. Minimize release to the environment.

#### Personal protection

Respiratory protection: Breathing of the vapors or dust particles may be hazardous. In the absence of appropriate engineering controls such as spot ventilation, ventilated enclosures, etc., workers should avail themselves of the appropriate NIOSH approved respiratory protection.

Hand protection: Adequate Protective Gloves should be worn.

Eye protection: Adequate safety glasses should be used.

Skin protection: Wear protective clothing, overall if necessary to limit the odour contamination of personal clothing. Individual washing routines should be followed after any potential contact.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

Appearance : Colour : Odour :	LIQUID PALE YELLOW TO YELLOW Characteristic strong odour according to the commercial description of the substance.
pH : Melting point/range (°C) : Initial boiling point/range (°C) : Flash point (closed cup) : Evaporation rate : Flammability (solid/gas) : Upper/lower flammability or explosive limits : Vapor pressure (At 20°C in mm Hg ) :	Not available Not available > 40°C = 59 Fahrenheit (= 15 Centigrade) Not available Not available
Calculated vapor pressure (At 20°C in mm Hg):	30.6
Vapour density : Relative density (d 20/20) : Water solubility (20°C) : Partition coef. (n-octanol/water) : Auto-ignition temperature (°C): Decomposition temperature : Viscosity : Explosive properties : Oxidizing properties : VOC Content less than:	Not available 0.954 - 0.974 Not applicable Not available Not available Not available Not available Not available Not available 75%

## **10 STABILITY AND REACTIVITY**

#### 10.1 Reactivity

No reaction known with water.

## According to Regulation HCS 2012

This Safety Data Sheet cancels and replaces all preceding SDS for this product.

## 10.2 Chemical stability

Presents no significant reactivity hazard. Normally stable even at elevated temperatures and pressures. Avoid temperatures above or near to the flash point. Not pyrophoric nor reactive with water. Does not undergo explosive decomposition, is shock stable, and is not an oxygen donor. Does not form explosive mixtures with other organic materials. Will not undergo hazardous exothermic polymerization.

- 10.3 Possibility of hazardous reactions Not known.
- <u>10.4 Conditions to avoid</u>
   Avoid temperatures above or at least 5 °C below flash point for any flammable liquids.
   Do not heat closed containers.
   Avoid contact with oxidizing agents.
- 10.5 Incompatible materials

Avoid strong oxidizing agents.

10.6 Hazardous decomposition products

Contact with water or storage under recommended conditions for one year should not produce dangerous decomposition products.

## **11 TOXICOLOGICAL INFORMATION**

This mixture has not been subjected to toxicological testing as an entity. According to available data on the constituents the health classification criteria are met.

## **12 ECOLOGICAL INFORMATION**

This mixture has not been subjected to ecotoxicological testing as an entity. According to available data on the constituents the environmental classification criteria are not met.

## **13 DISPOSAL CONSIDERATIONS**

## 13.1 Waste treatment methods

Product: The product should be handled according to the instructions given under sections 6, 7 and 8. Dispose of according to local or national regulations. The product should not be allowed to enter drains or the environment.

Contaminated packaging: Empty packaging should be disposed according to local or national regulations by an approved waste handling

## **14 TRANSPORT INFORMATION**

In case of accidental spillage or fire during transport, refer to instructions given under points 5, 6, 7 and 8 above.

UNO

UN-No:	1197
Proper Shipping Name:	EXTRACTS, FLAVOURING, LIQUID
Class:	3
Packing Group:	II

## According to Regulation HCS 2012

This Safety Data Sheet cancels and replaces all preceding SDS for this product.

## Land transport (ADR/RID)

UN-No: Proper Shipping Name:	1197 EXTRACTS, FLAVOURING, LIQUID (VAPOUR PRESSURE AT 50°C MORE THAN 110 KPA)
Class:	3
Packing group:	II

#### Sea transport (IMDG-Code)

UN-No:	1197
Proper Shipping Name:	EXTRACTS, FLAVOURING, LIQUID
Class:	3
Packing group:	II

#### Air transport (ICAO-IATA)

UN-No:	1197
Proper Shipping Name:	EXTRACTS, FLAVOURING, LIQUID
Class:	3
Packing group:	II

## **15 REGULATORY INFORMATION**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

NFPA Hazard Classification	
Health:	2
Flammability:	3
Reactivity:	0

This mixture contains no toxic chemical or chemicals subject to reporting requirements of Section 313 of Title III of the Superfund Amendements and Reauthorization Act of 1986 and 29 CFR Part 1910.1200.

## 15.2 Chemical Safety Assessment

No data available at this time.

## **16 OTHER INFORMATION**

### Revisions

01-Dec-2010: Version 6.1 - First version validated for publication 04-May-2012: Version 6.2 - Updates to sections 1, 2, 3, 8.3, 11, 12, 16. 20-Apr-2013: Version 6.3 - Updates to sections 1, 2, 3, 8.1, 14, 16. 07-July-2014: Version 6.4- Updates to section 2, 3, 14, 16. 30-May-2015: Version 6.5- Updates to section 2, 3, 7, 8, 9,13,14,16

Key literature references RIFM database OECD SIDS

## According to Regulation HCS 2012

This Safety Data Sheet cancels and replaces all preceding SDS for this product.

EU IUCLID Supplier information

Full text of phrases used under section 2

_		
S16	Keep away from sources of ignition - No smoking.	
S25	Avoid contact with eyes.	
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	
H225	Highly flammable liquid and vapour.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.	
P264	Wash thoroughly after handling.	
P240	Ground/bond container and receiving equipment.	
P241	Use rated explosion-proof electrical equipment.	
P242	Use only non-sparking tools.	
P243	Take precautionary measures against static discharge.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P303+P361+P353	IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P370+P378	In case of fire: Use appropriate fire extinguishers for fire control.	
P362	Take off contaminated clothing and wash before reuse.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P235	Keep cool.	
P332	If skin irritation occurs:	

Full text of phrases used under section 3

H225 H226 H302 H314 H315 H317 H318 H319 H336 H412	<ul> <li>Highly flammable liquid and vapour.</li> <li>Flammable liquid and vapour.</li> <li>Harmful if swallowed.</li> <li>Causes severe skin burns and eye damage.</li> <li>Causes skin irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Causes serious eye damage.</li> <li>Causes serious eye irritation.</li> <li>May cause drowsiness or dizziness.</li> <li>Harmful to aquatic life with long lasting effects.</li> </ul>
R10	Flammable.
R11	Highly flammable.
R22	Harmful if swallowed.
R34	Causes burns.

## According to Regulation HCS 2012

This Safety Data Sheet cancels and replaces all preceding SDS for this product.

R35	Causes severe burns.
R36	Irritating to eyes.
R38	Irritating to skin.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Firmenich, it is the user's obligation to determine conditions of safe use of the product.

Information contained in this document and related material is proprietary to Firmenich. Disclosure to third parties without the prior written consent of Firmenich except where required by applicable laws and regulations and/or reverse engineering are strictly prohibited.