

Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 1 (13)

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : GALBANUM RESOID 50PCT TEC BHT

SDS Number : R00000593661

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Ingredient used in Flavour and/or Fragrance preparations

1.3 Details of the supplier of the safety data sheet

Company : IFF Benicarló, S.L.

Avda. Felipe Klein 2 12580 BENICARLÓ

Spain

Telephone : +34964470212 Telefax : +34964473411 E-mail address : sds@iff.com

Responsible/issuing person **1.4 Emergency telephone number**

Refer to section 16 for country specific emergency contact number.

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters airways. Chronic aquatic toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 2 (13)

Hazard statements : H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/

spray.

P273 Avoid release to the environment.

P280 Wear protective gloves.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER or doctor/ physician.

P331 Do NOT induce vomiting.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Hazardous components which must be listed on the label:

• 7785-26-4, 80-56-8 alpha-Pinene

• 13466-78-9 3,7,7-trimethylbicyclo[4.1.0]hept-3-ene

• 138-86-3, 5989-27- limonene

5, 5989-54-8

2.3 Other hazards

None reasonably foreseeable.

3. Composition/information on ingredients

3.1 Substances

Not applicable, product is a mixture.

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION (EC) No 1272/2008)	[%]
	Registration number		
alpha-Pinene	7785-26-4, 80-56-8	Flam. Liq.3; H226	5 - 10
_	232-077-3, 201-291-9	Asp. Tox.1; H304	
		Skin Irrit.2; H315	

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 3 (13)

		Skin Sens.1B; H317 Aquatic Acute1; H400 Aquatic Chronic1; H410	
3,7,7- trimethylbicyclo[4.1.0]hept- 3-ene	13466-78-9 236-719-3	Flam. Liq.3; H226 Asp. Tox.1; H304 Skin Sens.1; H317 Skin Irrit.2; H315	5 - 10
limonene	138-86-3, 5989-27-5, 5989-54-8 205-341-0, 227-813-5, 227-815-6	Flam. Liq.3; H226 Skin Sens.1B; H317 Asp. Tox.1; H304 Aquatic Chronic1; H410 Skin Irrit.2; H315 Aquatic Acute1; H400	0,1 - 0,25
2,6-di-tert-butyl-p-cresol	128-37-0 204-881-4 01-2119565113-46, 01- 2119555270-46	Aquatic Chronic1; H410 Aquatic Acute1; H400	0,1 - 0,25
undeca-1,3,5-triene	16356-11-9 240-416-1	Skin Irrit.2; H315 Asp. Tox.1; H304 Aquatic Chronic1; H410 Aquatic Acute1; H400	0,025 - 0,1

For the full text of the R-phrases mentioned in this Section, see Section 16.

Components with workplace control parameters

Components	EC-No.	Concentration [%]
alpha-Pinene	232-077-3, 201-291-9	0 - 10
3,7,7-trimethylbicyclo[4.1.0]hept-3-ene	236-719-3	0 - 10

4. First aid measures

4.1 Description of first aid measures

General advice : Take Hazard and Precautionary phrases (section 2) into account.

If inhaled : Remove from exposure site to fresh air and keep at rest. If victim is

unconscious, remove foreign bodies from the mouth. If victim has stopped breathing, give artificial respiration. Obtain medical advice.

In case of skin contact : Remove contaminated clothes. Wash thoroughly with water (and

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 4 (13)

soap). Contact physician if symptoms persist.

In case of eye contact : Flush immediately with water for at least 15 minutes. Contact

physician if symptoms persist.

If swallowed : Rinse mouth with water and obtain medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbondioxide, dry chemical, foam.

Unsuitable extinguishing media : Do not use a direct waterjet on burning material.

5.2 Special hazards arising from the substance or mixture

Specific hazards during : Water may be ineffective.

firefighting

5.3 Advice for firefighters

Further information : Standard procedure for chemical fires.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid inhalation and contact with skin and eyes. A self-contained

breathing apparatus is recommended in case of a major spill.

6.2 Environmental precautions

Environmental precautions : Keep away from drains, surface- and groundwater and soil.

6.3 Methods and materials for containment and cleaning up

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 5 (13)

Methods for cleaning up

Clean up spillage promptly. Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Gross spillages should be contained by use of sand or inert powder and disposed of according to the local regulations.

6.4 Reference to other sections

Prevent spreading over a wide area (e.g. by containment or oil barriers).

7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

: Avoid excessive inhalation of concentrated vapors. Follow good manufacturing practices for housekeeping and personal hygiene. Wash any exposed skin immediately after any chemical contact, before breaks and meals, and at the end of each work period. Contaminated clothing and shoes should be thoroughly cleaned before re-use.

If appropriate, procedures used during the handling of this material should also be used when cleaning equipment or removing residual chemicals from tanks or other containers, especially when steam or hot water is used, as this may increase vapor concentrations in the workplace air. Where chemicals are openly handled, access should be restricted to properly trained employees.

Keep all heated processes at the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.

Advice on protection against fire and explosion

: Keep away from ignition sources and naked flame.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in a cool, dry, ventilated area away from heat sources. Keep containers upright and tightly closed when not in use.

7.3 Specific end use(s)

Specific use(s) : No information available.

8. Exposure controls/personal protection

8.1 Control parameters

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 6 (13)

Components with workplace control parameters

Components	EC-No.	Exposure limit(s)
alpha-Pinene	232-077-3, 201- 291-9	TWA
3,7,7-trimethylbicyclo[4.1.0]hept-3-ene	236-719-3	TWA

8.2 Exposure controls

Engineering measures

Where appropriate, use closed systems to transfer and process this material.

If appropriate, isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under negative air pressure relative to the rest of the plant.

Personal protective equipment

Respiratory protection

: Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures.

No respiratory protection is required during normal operations in a workplace where engineering controls such as adequate ventilation, etc. are sufficient.

If engineering controls and safe work practices are not sufficient, an approved, properly fitted respirator with organic vapor cartridges or canisters and particulate filters should be used:

a) while engineering controls and appropriate safe work practices and/or procedures are being implemented; or

b)during short term maintenance procedures when engineering controls are not in normal operation or are not sufficient; or

c)if normal operational workplace vapor concentration in the air is increased due to heat;

d)during emergencies; or

e)if engineering controls and operational practices are not sufficient to reduce airborne concentrations below an established occupational

exposure limit.

Hand protection : Avoid skin contact. Use chemically resistant gloves.

Eye protection : Use tight-fitting goggles, face shield or safety glasses with side

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 7 (13)

shields if eye contact might occur.

Hygiene measures : To the extent deemed appropriate, implement pre-placement and

regularly scheduled ascertainment of symptoms and spirometry testing of lung function for workers who are regularly exposed to

this material.

To the extent deemed appropriate, use an experienced air sampling expert to identify and measure volatile chemicals that could be present in the workplace air to determine potential exposures and to ensure the continuing effectiveness of engineering controls and

operational practices to minimize exposure.

Environmental exposure controls

General advice : Keep away from drains, surface- and groundwater and soil.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : conforms to standard

Odour Threshold : not determined

Flash point : 79 °C

Lower explosion limit : not determined Upper explosion limit : not determined Flammability (solid, gas) : not determined Oxidizing properties : not determined Auto-ignition temperature : not determined pH : not determined Melting point : not determined

Boiling point : not determined Vapour pressure : 0,27 hPa Calculated

Density : not determined
Water solubility : not determined
Partition coefficient: n- : not determined

octanol/water

Solubility in other solvents : not determined Viscosity, dynamic : not determined Viscosity, kinematic : not determined Relative vapour density : not determined

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 8 (13)

Evaporation rate : not determined

9.2 Other information

Refractive index : not determined Relative density : 1,1150 - 1,1450

10. Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Note: Presents no significant reactivity hazard, by itself or in contact

with water. Avoid contact with strong acids, alkali or oxidizing

agents.

10.4 Conditions to avoid

Conditions to avoid : Direct sources of heat.

10.5 Incompatible materials

Materials to avoid : Avoid contact with strong acids, alkali or oxidizing agents.

10.6 Hazardous decomposition products

Hazardous decomposition

products

: Carbon monoxide and unidentified organic compounds may be

formed during combustion.

11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Skin corrosion/irritation

alpha-Pinene : Species: Human

Result: No skin irritation Method: closed patch test Exposure time: 48 h

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 9 (13)

Species: Rabbit Result: Skin irritation Exposure time: 24 h

Serious eye damage/eye irritation

No lead substance

Respiratory or skin sensitisation

alpha-Pinene : maximisation study

Species: human

Result: Causes sensitisation. Test substance: 10% in petrolatum

Germ cell mutagenicity

Information on ingredients with chronic toxicity hazard(s) is available upon request.

Carcinogenicity

Information on ingredients with chronic toxicity hazard(s) is available upon request.

Reproductive toxicity

Information on ingredients with chronic toxicity hazard(s) is available upon request.

Target Organ Systemic Toxicant - Single exposure

Information on ingredients with chronic toxicity hazard(s) is available upon request.

Target Organ Systemic Toxicant - Repeated exposure

Information on ingredients with chronic toxicity hazard(s) is available upon request.

Aspiration hazard

No test data available. Ingredients with an aspiration hazard are identified in section 3.

12. Ecological information

12.1 Toxicity

Toxicity to daphnia and other aquatic invertebrates undeca-1,3,5-triene : EC50: 0,048 mg/l

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 10 (13)

Exposure time: 48 h

M-Factor

undeca-1,3,5-triene : 10

12.2 Persistence and degradability

12.3 Bioaccumulative potential

12.4 Mobility in soil

Mobility : No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological : There is no data available for this product.

information

13. Disposal considerations

13.1 Waste treatment methods

Product : Dispose of according to local regulations. Avoid disposing into

drainage systems and into the environment.

Contaminated packaging : Empty containers should be taken to an approved waste handling

site for recycling or disposal.

14. Transport information

ADR

UN number : 3082

Description of the goods : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(ALPHA-PINENE)

Labels : 9
Packing group : III
Environmentally hazardous : yes

IATA

UN number : 3082

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 11 (13)

Description of the goods : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(ALPHA-PINENE)

Labels : 9
Packing group : III
Environmentally hazardous : yes

IMDG

UN number : 3082

Description of the goods : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(ALPHA-PINENE)

Labels : 9 Packing group : III

Marine pollutant : yes (ALPHA-PINENE)

Special precautions for

user

: No special precautions required.

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Water contaminating class

(Germany)

WGK 3highly water endangering

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Further information

In December 2003, the National Institute for Occupational Safety and Health ("NIOSH") published an Alert

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 12 (13)

on preventing lung disease in workers who use or make flavorings [NIOSH Publication Number 2004-110]. In August 2004, the United States Flavor and Extract Manufacturers Association (FEMA) issued a report entitled "Respiratory Safety in the Flavor Manufacturing Workplace".

Both of these reports provide recommendations for reducing employee exposure and for medical surveillance in the workplace. The recommendations in these reports are generally applicable to the use of any chemical in the workplace and you are strongly urged to review both of these reports.

The report published by FEMA also contains a list of "high priority" chemicals. If any of these chemicals are present in this product at a concentration >= 1.0% due to an intentional addition by IFF, the chemical(s) will be identified in this safety data sheet.

According to Regulation (EC) No. 1907/2006 the information in this safety data sheet is based on the properties of the material known to IFF at the time the data sheet was issued. The safety data sheet is intended to provide information for a health and safety assessment of the material and the circumstances, under which it is packaged, stored or applied in the workplace. For such a safety assessment International Flavors & Fragrances holds no responsibility. This document is not intended for quality assurance purposes.

Emergency telephone number

Austria	+43 1 406 43 43
Belgium	+32 70 245 245
Bulgaria	+359 2 9154 233
Croatia	(+385 1) 2348342
Czech Republic	+420 224 919 293 / +420 224 915 402
Denmark	+45 82 12 12 12
Estonia	16662 (National), International (+372) 626 93 90
Finland	+358 9 471977
France	+ 33 (0)1 45 42 59 59
Germany	+31 13 4642 211
Greece	+31 13 4642 211
Hungary	(+36-80) 201-199
Iceland	+354 543 2222
Ireland	+353 1 8092566 / +353 1 8379964
Italy	+39 06 68593726
Latvia	+371 67042473
Lithuania	+370 5 236 20 52 or +370 687 53378
Luxembourg	+352 8002 5500
Malta	+356 21224071
Netherlands	+31 30 2748888 (Only for the purpose of informing medical personnel in
	cases of acute intoxications).

Version : 5.0

Revision Date : 23.08.2017



Product GALBANUM RESOID 50PCT TEC BHT

Print Date 11.05.2018 Page 13 (13)

Norway	+47 22 59 13 00	
Poland	+31 13 4642 211	
Portugal	808 250 143	
Poland	+31 13 4642 211	
Portugal	808 250 143	
Romania	+31 13 4642 211	
Slovakia	+31 13 4642 211	
Slovenia	+31 13 4642 211	
Spain	+34 91 562 04 20 (only for the purpose of informing medical personnel in	
	cases of acute intoxications).	
Sweden	+46 112	
United Kingdom	For medical professionals only +44 845 46 47 (England and Wales)	
	+ 44 8454 24 24 24 (Scotland)	

Version : 5.0

Revision Date : 23.08.2017